

Order No. Model No.	500005128 REV24-WC	
Notes:		

# Section 10309 - Manufactured Electric Fireplaces

### **PART 1 GENERAL**

### 1.1 SECTION INCLUDES

- A. Manufactured electric fireplaces.
- B. Accessories

### 1.2 RELATED SECTIONS

A. Section 06100 - Rough Carpentry: Wood framed rough opening and enclosure.

### 1.3 REFERENCES

- A. UL 2021
- B. CSA C22.2 No. 46

### 1.4 SUBMITTALS

- A. Submit under provisions of Section 01300.
- B. Product Data: Manufacturer's data sheets on each product to be used, including:
  - 1. Preparation instructions and recommendations.
  - 2. Storage and handling requirements and recommendations.
  - 3. Installation methods.
- C. Manufacturer's Certificates: Certify products meet or exceed specified requirements.
- D. Manufacturer's warranty.

### 1.5 DELIVERY, STORAGE, AND HANDLING

- A. Store products in manufacturer's unopened packaging until ready for installation.
- B. Protect materials from exposure to moisture. Do not deliver until after wet work is complete and dry.

### 1.6 WARRANTY

A. Provide the manufacturer's 2-year limited warranty on electrical components.

### PART 2 PRODUCTS

### 2.1 ACCEPTABLE MANUFACTURERS

- A. Pre-fabricated Electric Fireplace:
  - Base: Dimplex Electric Fireplace Glen Dimplex Americas

1367 Industrial Road

Cambridge ON N3H 4W3

1-888-346-7539

www.dimplex.com

- 2. Substitutions not permitted
- 3. Requests for substitutions will be considered in accordance with provisions of Section 01600.



Order No. 500005128
Model No. REV24-WC
Notes:

## Section 10309 - Manufactured Electric Fireplaces

### 2.2 ELECTRIC FIREPLACES

### A. General:

- 1. Provide all components and accessories required for a complete, functional unit.
- 2. UL or CSA listed.

### B. Pre-fabricated Electric Fireplace:

- 1. Base Product:
  - a) Dimplex Built-in Electric Firebox
  - b) Material Number: 500005128
  - c) Model Number: REV24-WC
  - d) Regulatory model number: 6909990400
- 2. Description: Revillusion 24" Built-in/Fireplace Insert Electric Firebox, Weathered Concrete with Glass and Plug Kit
- 3. Dimensions:
  - a) Width: 24-1/4" / 64.0 cmb) Height: 22-7/8" / 58.1 cmc) Depth: 12-1/8" / 30.7 cm
- 4. Framing Dimensions:
  - a) Width: 24-5/8" / 62.6 cmb) Height: 22-3/8" / 56.8 cmc) Depth: 12-1/2" / 31.8 cm
- 5. Weight:
  - a) Product: 56.8 lbs / 25.7 kgb) Packaged: 60 lbs / 27.2 kg
- 6. Electrical:
  - a) Volts: 120b) Watts: 1,500
  - c) Flame Only Watts: 40
  - d) BTUs: 5,118
- 7. Venting: Non-venting
- 8. Operation: Flame only, flame and heat
- 9. Heating: Fan-forced circulation, Comfort\$aver
- 10. Liner: Steel
- 11. Standard features:
  - a) Self-trimming design with flange to finish rough openings
  - b) Patented flame technology create brighter and more random flames



Order No. 500005128
Model No. REV24-WC

Notes:

# Section 10309 - Manufactured Electric Fireplaces

- c) Partially frosted acrylic panel highlights flame without any reflections
- d) Full weathered concrete surround, 270°
- e) Customizable firebox hues, mood lighting to adjust firebox light level
- f) Powerful heating capabilities use as part of primary heat plan
- g) Direct-wire capabilities 120V
- h) Comfort\$aver® Heating System
- i) Front glass panel
- i) Eco/Boost Mode

### 12. Control options:

- a) Multi-function remote control
- b) Built-in touch controls

### 13. Optional Accessories:

a) Installation Trim Kit - X-RBF24TRIM36, X-RBF24TRIM40

### PART 3 EXECUTION

#### 3.1 INSPECTION

- A. Do not begin installation until substrates have been properly prepared.
- B. If substrate preparation is the responsibility of another installer, notify Architect of unsatisfactory preparation before proceeding.
- C. Verify proper power supply and fuel source are available.

### 3.2 PREPARATION

- A. Clean surfaces thoroughly prior to installation.
- B. Prepare surfaces using the methods recommended by the manufacturer for achieving the best result for the substrate under the project conditions.

### 3.3 INSTALLATION

- A. Install in accordance with manufacturer's instructions and requirements of authorities having jurisdiction.
- B. Use manufacturer's guidelines for minimum clearances to combustibles, walls, and finishes.
- C. Anchor all components firmly in position for long life under hard use.
- D. Upon completion of installation, visually inspect all exposed surfaces. Touch up scratches and abrasions with touch up paint recommended by the manufacturer; make imperfections invisible to the unaided eye from a distance of 5 feet (1.5 m).

### 3.4 PROTECTION


- A. Protect installed products until completion of project.
- B. Touch-up, repair or replace damaged products before Substantial Completion.


Order No.	500005128
Model No.	REV24-WC
Notes:	

# Section 10309 - Manufactured Electric Fireplaces

## **Framing Dimensions:**


	REV24-WC		
А	12-1/2" (31.8 cm)		
В	24-5/8" (62.6 cm)		
С	22-3/8" (56.8 cm)		
D	22-1/8" (56.2 cm)		
Е	12-1/8" (30.7 cm)		
F	23-3/8" (59.5 cm)		
G	25-1/4" (64.0 cm)		
Н	19" (48.3 cm)		
I	22-7/8" (58.1 cm)		
J	47-3/4" (121.3 cm)		
K	33-3/4" (85.7 cm)		
L	33-3/4" (85.7 cm)		





- The Revillusion™ Electric Fireplace/ Fireplace Insert does not require any special venting.
- 2. To build the rough-in opening, follow the framing dimensions below.

**NOTE:** The materials used for the finished surround must be cut to precise dimensions (dimensions B & C) as the 1/4" (0.6 cm) self trimming flange is only to create a finished appearance.



### **Accessory Dimensions:**

### FINISHED TRIM DIMENSIONS

Trim Kit	Α	В	С
RBF24TRIM36 - 36" Black Installation Trim	36" (91.4 cm)	30" (76.2 cm)	
RBF24TRIM40 - 40" Black Installation Trim	40" (101.6 cm)	30" (76.2 cm)	2"
RBF30TRIM38 - 38" Black Installation Trim	38" (96.5 cm)	29-5/8" (75.4 cm)	(5.08 cm)
RBF30TRIM44 - 44" Black Installation Trim	44" (111.8 cm)	32-5/8" (83.0 cm)	



Scan for more information on dimensions, accessories, technical details.

To view full series visit: dimplex.com

1-800-668-6663

